



# Sweet Air™

## VENT STACK ODOR ELIMINATOR

For residential and commercial vent stacks

Offensive odors including hydrogen sulfide gas are produced in residential & commercial drain pipes and septic systems. The Sweet Air™ vent filter is your answer to eliminate plumbing or septic odors. Sweet Air™ is inexpensive and can be easily installed on existing vent stacks. Activated carbon "scrubs" the vent discharge putting an end to unpleasant odors from house, septic, and portable toilet vents.



VENT  
STACK  
ODORS

## STOP OFFENSIVE ODORS



from sewer and septic tank vent stacks that drift onto patios and into windows with Sweet Air™ Odor Eliminator.

## THE SWEET AIR™ SYSTEM



- UV stabilized, HI-Impact ABS construction
- a** Twist Top Cap for easy activated carbon maintenance
- b** Vented lid and chamber
- c** Vents for unrestricted airflow
- d** Activated carbon mesh pouch in chamber
- e** Ventilated chamber bottom with universal connector fits 3" or 4" Schedule 40 vent stack
- Easy no-tool installation
- No more offensive odors
- No more spoiled patio parties
- No more foul air drifting into open windows



## HOW IT WORKS

1. Unpleasant odors raise from house or septic stack vent
2. Odors pass thru activated carbon which "scrubs" and removes odor
3. Clear, odor-free air leaves Sweet Air™ Odor Eliminator



Attractive, at-a-glance packaging that quickly and thoroughly tells the Sweet Air™ story.



# Sweet Air™

## odor eliminator



**a** Twist Top Cap for easy activated carbon maintenance

**b** Activated carbon chamber vented lid

**c** Vents for unrestricted airflow

**d** Activated carbon chamber

**e** Activated carbon mesh pouch in chamber

**8oz. carbon package included and sealed for freshness.**  
Replace carbon about every 1-5 years or as needed. Refills available where you purchase Sweet Air™. **Do not use more than 8oz of carbon in the chamber.**

**f** Ventilated chamber bottom with universal connector fit 3" or 4" Schedule 40 vent stack

(For 2" vent stack use Schedule 40 2x2 coupler. For 1-1/2" vent stack use a Schedule 40 2" hub x 1-1/2" slip reducer. Not included)

Max. air flow 47 CFM



## how it works

1. Unpleasant odors raise from house or septic stack vent
2. Odors pass thru activated carbon which "scrubs" and removes odor
3. Clear, odor-free air leaves Sweet Air™ Odor Eliminator



**Sweet Air™ is your answer to eliminating offensive odors**



# Sweet Air™

## is easily installed

**VENT  
STACK  
ODORS**



1. Locate the vent stack pipe on your roof or septic tank.

2. Glue the **Sweet Air™** Odor Eliminator to the vent stack using solvent weld glue.

Universal connector fits 3" or 4" Schedule 40 vent stack. (For 2" vent stack use Schedule 40 2x2 coupler. For 1-1/2" vent stack use a Schedule 40 2" hub x 1-1/2" slip reducer. Not included - available at your home center or hardware store.)

3. Open the **Sweet Air™** by twisting off the cover and removing the cover and ventilated chamber lid.

4. Remove the activated carbon bag from the chamber.

**Open only the airtight, clear poly bag leaving the mesh bag containing the activated carbon. Discard the clear poly bag.**

5. Insert the activated carbon in the mesh bag into the chamber. Push the mesh bag to the base of the chamber - leave no gaps between the chamber wall and the mesh bag.

6. Replace the **Sweet Air™** chamber lid and top, twisting to lock it into place.



Activated carbon may be replaced by removing the twist off cover and vented chamber lid. Discard old carbon and replace with new Genuine **Sweet Air™** replacement carbon pack available where you purchased your **Sweet Air™**. Carbon pack should be replaced every 1-5 years or as needed. More heavily occupied homes will require more frequent replacement than homes with lower occupancy.

**Enjoy the outdoors without unpleasant odors**